






Catalog#	LED Spacing	Lens	Length	Power	Weight
GRX-(2700, 3000, 4000)-15D-300	3" (75 mm)	15°	12" (300 mm)	12 Watts	0.9 lb. / 400g
GRX-(2700, 3000, 4000)-15D-600	3" (75 mm)	15°	24" (600 mm)	24 Watts	1.7 lb. / 750g
GRX-(2700, 3000, 4000)-15D-1200	3" (75 mm)	15°	48" (1200 mm)	48 Watts	3.1 lb. / 1400g

GRX Series Specifications	
Voltage: 24VDC	
Current: 125mA Per LED	
Power: 3W Per LED	
IP Rating: 66	
CRI Value: 85	
Color	Output
2700K	150 Lm Per LED
3000K	160 Lm Per LED
4000K	180 Lm Per LED



TOKISTAR LIGHTING INC.

1015 E. DISCOVERY LANE
ANAHEIM, CA 92801
TEL: 714 772 7005 FAX: 714 772 7014
email: info@tokistar.com Website: tokistar.com

Gradient GRX Series Submittal		No.	Part	Material
Catalog#: GRX-(2700K, 3000K, 4000K)-15D-XXXX		1	Extrusion	Anodized Aluminum
Date: December 17, 2018		2	Cover	Anodized Aluminum
Drawn By: R. Cordova		3	Mounting Bracket	SUS
Scale: 1:4		4	LED Lens	PC
		5	Power Cable	PVC Insulation (#18 AWG x 2 / # 22 AWG x 2)
		6	Power Cable	PVC Insulation (#18 AWG x 2 / # 22 AWG x 2)
		7	Connectors	Nylon (waterproof) with IP67 rating