Gen II LED Hard Strip

cool to the touch and provide 120° beam spread.

Gen II LED Hard Strip is a new and improved energy efficient linkable strip, that provides a smooth, even lighting, eliminating any hot spots. Encased in an aluminum casing, the LED's are









FEATURES

- 50,000 hours life
- Use high brightness 0.5W Epistar LEDs as lighting source
- Even light distribution with 120° viewing angle
- Available in 4 sizes
- Convenient connector

between two strips


· Diffused frosted lens to reduce glare

- Display cases
- Cabinet interiors
- Work stations
- Interior decorative lighting


		SPECIFI	CATIONS		
		Size 1	Size 2	Size 3	Size 4
Product code	LV-HS-PD20-24V-YY-XX	30	50	100	120
Electrical	Input Voltage	24V DC			
	Power Consumption	4W	7W	13W	16W
Specs	Colour Temp: Neutral White	4200K +/- 200K			
	Colour Temp: Warm White	3000K +/- 200K			
	Lumens (LM): Neutral White	400	664	1066	1150
	Lumens (LM): Warm White	380	621	1036	1100
	Viewing Angle	120°			
LED	Life Span	50,000 Hours			
	Qty. per strip	36	60	132	156
Design	Size	11.8" (300mm)	19.7" (500mm)	39.4" (1000mm)	47.3" (1200mm)
	Product Material	Aluminum			
	Operating Temperature	-35°C to 50°C			
	Mounting	2 pieces of 0° mounting clips and one end cap			
Warranty	3 years limited				
Approvals	cETLus for indoor use				

NOTE: Each Hard Strip bar ships with 2pcs of 0° mounting clips and one end cap.

MOUNTING OPTIONS



PRODUCT CODES



APPLICATIONS

- Under counter

NON DIMMABLE DRIVERS DIMMABLE DRIVERS

MLDRE-40-24-DM

Max recommended load 36W, min. 8W LED Hard Strip 6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

MLDRE-96-24-DM

Max recommended load 90W, min. 8W LED Hard Strip 6.77" x 2.67" x 1.26" (171 x 68 x

MLDR-120-24

Four lengths available 11.8" (300mm), 19.7" (500mm), 39.4" (1000mm), 47.3" (1200mm)

Indoor/Outdoor driver Max, recommended load 90W per single tap, 120W combined two secondary taps.

120W hardwire Input: 100 - 240V AC

Output: 24V DC 10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

MLDR-20-24JB

x 38.1mm)

Indoor driver Max recommended load 18W 20W hardwire Input: 100 - 240V AC Output: 24V DC 4 1/8" x 4 1/8" x 1 1/2" (104.8 x 104.8

ACCESSORIES



LV-HS-PD20-PF1-12 LV-HS-PD20-PF1-39

12" Power Feed for LED Hard Strip single colour, Bar – DC plug power supply

LV-HS-PD20-PC1-3



3" Power Connector for LED Hard Strip Single Colour, Bar – Bar



LV-HS-CN-3DC

Connector for Hard Strip, with 12" wire lead and 3 DC connectors

LV-HS-CN-2DC

LV-HS-MCTR

Connector for Hard Strip, with 12" wire lead and 2 DC connectors



LV-HS-MC45

Mounting clip 45° (2pk) Rotary Mounting clip (2pk)



LV-HS-PD20-PF1-HW

39" Power Feed for LED Hard 39" Power Feed for LED Hard Strip single colour, Bar – DC Strip single colour, Bar – Hard wire power supply plug power supply

LV-HS-EC



12" Power Connector for LED Hard Strip single colour, Bar – Bar



LV-HS-MC0

End Cap for LED Hard Strip Mounting clip (2pk)



LV-HS-PD20-PC1-39

39" Power Connector for LED Hard Strip single colour, Bar – Bar



LV-HS-MC30

Mounting clip 30° (2pk)