



LDRCC-40 Specifications

Input Range: 100~277 VAC
 Frequency Range: 50/60 Hz
 Output: 3-57 VDC
 Current: 700mA
 Max. Output Power: 40W
 Protection: Overload, Overcurrent, Short Circuit
 Over Temperature, Mis-Wiring protection (auto shutdown)
 Operating Temperature: -40°C to +50°C

Mechanical Specifications

Housing Material: Aluminum
 Dimensions: 5" x 2.6" x 1"
 Weight: .38 lbs / 170g
 Enclosure Rating: IP21
 Mounting: Flange Mount/Stud Mount
 Input/Output Connectors: Wago 253/16-20AWG

Safety Standards

Listed to UL8750, UL Class 2, Class P
 EMI Compliance: FCC 47CFR Part 15 Class B

LED Capacity

2 to 18 GRHB 2.1 Watt LEDs
 1 to 18 O'Links / I'Links 2.1 Watt LEDs



TOKISTAR LIGHTING INC.

1015 E. DISCOVERY LANE
 ANAHEIM, CA 92801
 TEL: 714 772 7005 FAX: 714 772 7014
 email: info@tokistar.com Website: tokistar.com

Description: LDRCC-40 LED Driver Submittal

Date: December 1, 2018

Scale: NTS

Drawing #: 120118-RC-A

Drawn By: R. Cordova