



**LDRCC-40 Specifications**

Input Range: 100~277 VAC  
 Frequency Range: 50/60 Hz  
 Output: 3-57 VDC  
 Current: 700mA  
 Max. Output Power: 40W  
 Protection: Overload, Overcurrent, Short Circuit  
 Over Temperature, Mis-Wiring protection (auto shutdown)  
 Operating Temperature: -40°C to +50°C

**Mechanical Specifications**

Housing Material: Aluminum  
 Dimensions: 5" x 2.6" x 1"  
 Weight: .38 lbs / 170g  
 Enclosure Rating: IP21  
 Mounting: Flange Mount/Stud Mount  
 Input/Output Connectors: Wago 253/16-20AWG

**Safety Standards**

Listed to UL8750, UL Class 2, Class P  
 EMI Compliance: FCC 47CFR Part 15 Class B

**LED Capacity**

2 to 18 GRHB 2.1 Watt LEDs  
 1 to 18 O'Links / I'Links 2.1 Watt LEDs



**TOKISTAR LIGHTING INC.**

1015 E. DISCOVERY LANE  
 ANAHEIM, CA 92801  
 TEL: 714 772 7005 FAX: 714 772 7014  
 email: info@tokistar.com Website: tokistar.com

Description: LDRCC-40 LED Driver Submittal

Date: December 1, 2018

Scale: NTS

Drawing #: 120118-RC-A

Drawn By: R. Cordova