

LED eStrip

LED eStrip is our most versatile linear lighting product. Now with 3014 type LEDs, LED eSTRIP is brighter and better than ever!



FEATURES

- 40,000 hours life
- Safe low voltage (24V)
- Virtually maintenance free
- Ultra low power consumption
- Available in 90' spools (custom cuts available)
- Crushproof to 100psi
- Field cuttable
- Inter-connectable
- Highly flexible (min. bend radius 1.5")
- Indoor/outdoor use
- Impact resistant
- Six brilliant colours
- Dimmable
- 2 year limited warranty

APPLICATIONS

- Building outlines
- Coves
- Stairway and aisle lighting
- Signage
- Backlit panels
- Decks
- Edgelit glow
- Emergency lighting
- Pathway lighting
- Billboards
- Highlighting architectural features
- Over/Under cabinets

SPECIFICATIONS

Electrical	24V DC, 0.96W/ft
Viewing Angle	120°
LED Life	40,000 hours
LED Spacing	1" (25.4mm)
Maximum Length	90' (27.4m)
Custom Cuttable	6" (152.4mm)
Lumen Output	61 Lumens per ft. 5800K 55 Lumens per ft. 3000K
LED Colours	Amber, Red, Blue, Pure Green, 5800K, 3000K
Min/Max Surface Temperature for Mounting	-40°C - 40°C (-40°F - 104°F)
PVC Body Colour	Clear
Dimensions	.25" X .5" (6mm x 12mm)
Approvals	cETLus

PRODUCT CODES

90Ft spools

MLS - **ESTRIP** - **YY** - 1 - 24 - 90FT

LED eSTRIP

LED COLOUR

3000K
5800K
AM - Amber
BL - Blue
PG - Pure Green
RD - Red


Custom cuts

MLS - **ESTRIP** - **YY** - 1 - 24 - **XX**

LED eSTRIP

LED COLOUR

3000K
5800K
AM - Amber
BL - Blue
PG - Pure Green
RD - Red



ACCESSORIES



MLS-BFMS-15
Indoor Power connector, with SJTW-2 1.5 ft wires for through wall connections 1/4" x 1/2" (6mm x 12mm) Comes with end cap



MLS-BFMB-72
Outdoor 6' Power connector for burial connections, 1/4" x 1/2" (6mm x 12mm) Comes with end cap
MLS-BFMS-72
Indoor 6' Power connector for through wall connections



MLS-BFMB-120
Outdoor Power connector, with SJTW-2 12 ft wires for burial connections, 1/4" x 1/2" (6mm x 12mm) Comes with end cap
MLS-BFMS-120
Indoor 12' Power connector for through wall connections



MLS-STP-2BR
Outdoor 2' Step cord for burial connections
MLS-STP-2CL
Indoor 2' Step cord (shown) for through wall connections



MLS-STP-12BR
Outdoor 12' Step cord (shown) for burial connections
MLS-STP-12CL
Indoor 12' Step cord for through wall connections



MLS-EFBR
Outdoor Step cord for burial connections
MLS-EFSN
Indoor Step cord (shown) for through wall connections



LMSII-001
Terminal block and junction box for connection to additional lengths of power cable if needed



MLS-BFLN
L type connector, 1/4" X 1/2" (6mm x 12mm)



MLS-BFSN
In-Line connector set, male and female, 1/4" X 1/2" (6mm x 12mm)



MLS-BFTD
T type connector, 1/4" X 1/2" (6 x 12mm), male connector in bottom



MLS-SFHN
Cutting end cap, 0.25" X 0.5" (6mm x 12mm)



MLS-BFTR
T type connector, 1/4" X 1/2" (6 x 12mm), male connector in right or left



MLS-SNPN
Wood nail clips, 1/4" X 1/2" (6mm x 12mm)



MLS-SMPN
Tie wrap and mounting saddle



NN-C10-POLY
For outdoor use
NN-C10-8
For indoor use. Clear PVC mounting "U" channel



MLS-BFXN
X type connector, 1/4" X 1/2" (6mm x 12mm)



MLS-BFDN
6 x 12mm splice kit (pins, pad and shrink tube)

INDOOR/OUTDOOR DIMMABLE DRIVERS

MLDRE-40-24-DM
Max 37.5' (11.4m)
Min 8 Watts, 9' LED eStrip (2.7m)
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

MLDRE-96-24-DM
Max 90' (27.4m)
Min 8 Watts, 9' LED eStrip (2.7m)
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

NOTE: For outdoor installations, please add E-KO-SR strain relief (2pcs/driver).

NON DIMMABLE DRIVERS

MLDR-120-24
Indoor/Outdoor driver
Max 90' (27.4m) per single tap
Max 120' (36.5m) combined 2 secondary taps
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

MLDR-20-24JB
Indoor driver
Max recommended load 18W LED eStrip
Input: 100 - 240V AC
Output: 24V DC
20 Watts
4 1/8" x 4 1/8" x 1 1/2" (104.8 x 104.8 x 38.1mm)

High Power LED eStrip

New High Power eStrip with twice the lumen output of our regular eSTRIP!



FEATURES

- 40,000 hours life
- Safe low voltage (24V)
- Virtually maintenance free
- Ultra low power consumption
- Available in 40' spools (custom cuts available)
- Crushproof to 100psi
- Field cuttable
- Inter-connectable
- Highly flexible (min. bend radius 1.5")
- Indoor/outdoor use
- Impact resistant
- Dimmable
- 2 year limited warranty

APPLICATIONS

- Building outlines
- Coves
- Stairway and aisle lighting
- Signage
- Backlit panels
- Decks
- Edgelit glow
- Emergency lighting
- Pathway lighting
- Billboards
- Highlighting architectural features
- Over/Under cabinets

PRODUCT CODES

40Ft spools

MLSHP - ESTRIP - YY - 1 - 24 - 40FT

HIGH POWER
LED eStrip

LED COLOUR
3000K
5800K

Custom cuts


MLSHP - ESTRIP - YY - 1 - 24 - XX

HIGH POWER
LED eStrip

LED COLOUR
3000K
5800K

SPECIFICATIONS

Electrical	24V DC, 2.2W/ft
Viewing Angle	120°
LED Life	40,000 hours
LED Spacing	1" (25.4mm)
Maximum Length	40' (12m)
Custom Cuttable	6" (152.4mm)
Lumen Output	155 Lumens per ft. 5800K 137 Lumens per ft. 3000K
LED Colours	5800K, 3000K
Min/Max Surface Temperature for Mounting	-40°C - 40°C (-40°F - 104°F)
PVC Body Colour	Clear
Dimensions	.25" X .5" (6mm x 12mm)
Approvals	cETLus



ACCESSORIES



MLS-BFMS-15
Indoor Power connector, with SJTW-2 1.5 ft wires for through wall connections 1/4" x 1/2" (6mm x 12mm) Comes with end cap



MLS-BFMB-72
Outdoor 6' Power connector for burial connections, 1/4" x 1/2" (6mm x 12mm). Comes with end cap
MLS-BFMS-72
Indoor 6' Power connector for through wall connections



MLS-BFMB-120
Outdoor Power connector, with SJTW-2 12 ft wires for burial connections 1/4" x 1/2" (6mm x 12mm) Comes with end cap
MLS-BFMS-120
Indoor 12' Power connector for through wall connections



MLS-STP-2BR
Outdoor 2' Step cord for burial connections
MLS-STP-2CL
Indoor 2' Step cord (shown) for through wall connections



MLS-STP-12BR
Outdoor 12' Step cord (shown) for burial connections
MLS-STP-12CL
Indoor 12' Step cord for through wall connections



MLS-EFBR
Outdoor Step cord for burial connections
MLS-EFSN
Indoor Step cord (shown) for through wall connections



LMSII-001
Terminal block and junction box for connection to additional lengths of power cable if needed



MLS-BFLN
L type connector, 1/4" X 1/2" (6mm x 12mm)



MLS-BFSN
In-Line connector set, male and female, 1/4" X 1/2" (6mm x 12mm)



MLS-BFTD
T type connector, 1/4" X 1/2" (6 x 12mm), male connector in bottom



MLS-SFHN
Cutting end cap, 0.25" X 0.5" (6mm x 12mm)




MLS-BFTR
T type connector, 1/4" X 1/2" (6 x 12mm), male connector in right or left



MLS-SNPN
Wood nail clips, 1/4" X 1/2" (6mm x 12mm)



MLS-SMPN
Tie wrap and mounting saddle



NN-C10-POLY
For outdoor use
NN-C10-8
For indoor use. Clear PVC mounting "U" channel



MLS-BFXN
X type connector, 1/4" X 1/2" (6mm x 12mm)



MLS-BFDN
6 x 12mm splice kit (pins, pad and shrink tube)

INDOOR/OUTDOOR DIMMABLE DRIVERS

MLDRE-40-24-DM

Max 16' (4.87m)
Min 8 Watts, 4' LED eStrip (1.2m)
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

MLDRE-96-24-DM

Max 40' (12.1m)
Min 8 Watts, 4' LED eStrip (1.2m)
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

NOTE: For outdoor installations, please add E-KO-SR strain relief (2pcs/driver)

NON DIMMABLE DRIVERS

MLDR-120-24

Indoor/Outdoor driver
Max 40' (12.1m) per single tap
Max 54' (16.46m) combined 2 secondary taps
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

MLDR-20-24JB

Indoor driver
Max recommended load 18W LED eStrip
Input: 100 - 240V AC
Output: 24V DC
20 Watts
4 1/8" x 4 1/8" x 1 1/2" (104.8 x 104.8 x 38.1mm)

RGB LED eStrip

RGB eSTRIP utilizes RGB LEDs allowing you to produce dramatic colour change effects for building outlines, architectural features or anywhere eye catching colour changing display lighting is needed.



FEATURES

- 40,000 hours life
- Safe low voltage (24V)
- Virtually maintenance free
- Ultra low power consumption
- Available in 40' spools (custom cuts available)
- Crushproof to 100psi
- Field cuttable
- Inter-connectable
- Highly flexible (min. bend radius 1.5")
- Indoor/outdoor use
- Impact resistant
- Dimmable
- 2 year limited warranty

APPLICATIONS

- Building outlines
- Coves
- Stairway and aisle lighting
- Signage
- Backlit panels
- Decks
- Edgelit glow
- Emergency lighting
- Pathway lighting
- Billboards
- Highlighting architectural features
- Over/Under cabinets

PRODUCT CODES

40Ft spools

MLS - ESTRIP - RGB - 1 - 24 - 40FT


Custom cuts

MLS - ESTRIP - RGB - 1 - 24 - XX

NOTE: Sold in 2ft. increments

SPECIFICATIONS

Electrical	24V DC, 2.2W/ft
Viewing Angle	120°
LED Life	40,000 hours
LED Spacing	1.3" (33mm)
Maximum Length	40' (12m)
Custom Cuttable	8" (198mm)
LED Colours	RGB
Min/Max Surface Temperature for Mounting	-40°C - 40°C (-40°F - 104°F)
PVC Body Colour	Clear
Dimensions	.3" X .6" (7.6mm x 15mm)
Approvals	cETLus



ACCESSORIES



MLS-BFTN
Female connector



MLS-BTMN
Male connector



MLS-BTSN
In line connector



MLS-BTMCJ-1.5
1.5' Power connector



MLS-BTMCJ-6
6' Power connector



MLS-BTMC-G4-SI
Signal in connector for
RGB eStrip connection to
outdoor signal amplifier



MLS-BTMC-G4-SO
Signal out connector for RGB
eStrip connection to outdoor
signal amplifier



LV-CN-G2
Power feed connector for
connection to outdoor
signal amplifier



MLS-STCN
Cutting end cap



MLS-STFN
Female end cap



MLS-STPV-T
Clear PVC mounting
"U" channel (1M)



MLS-SNPT
Wood nail clips,
1/4" X 1/2" (6mm x 12mm)



MLS-C-6
Tie wrap



MLS-MX-1
Allen key



TCJ-E06
6' (1.8m) Extension cord
TCJ-E30
30' (9.1m) Extension cord



MLS-TCJ-EI6-M
LED RGB eStrip 6" Flex
Connector



LT-09S-RF
6 Key RGB "touch"
controller 12/24V DC



LN-CON-WIFI-3CH-XV
WiFi controller for RGB, c/w
RF remote 12/24VDC



LV-ZJFFS-3CH-6INW
Outdoor RGB signal
amplifier

NON DIMMABLE DRIVERS

MLDR-120-24

Indoor/Outdoor driver
Max 40' (12.1m) per single tap
Max 54' (16.46m) combined 2 secondary taps
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

MLDR-20-24JB

Indoor driver
Max recommended load 18W RGB LED eStrip
Input: 100 - 240V AC
Output: 24V DC
20 Watts
4 1/8" x 4 1/8" x 1 1/2" (104.8 x 104.8 x 38.1mm)