Outdoor Wall Sconce

A contemporary style wall sconce suitable for interior and exterior use. Available in three finishes and three interchangeable covers to suit a variety of applications,



• Housing: Rugged aluminum construction

Input Voltage

Lumen Output

Efficacy (LM/W)

Dimmable Beam Angle

Туре

Life Span

Finish

Material

Mounting

Dimensions (Inches)

Dimensions (Millimeters)

Operating Temperature

Approved Location

CRI

Power Consumption **Colour Temperature**

- 120V 277V AC input voltage
- Lumen output 1300LM
- CRI 80+

Product Code

Electrical

Specs

LED

Design

Warranty

Approvals

- LED life: 50,000 hours
- Powder coated finish

- 120° beam angle ADA compliant
- Finishes: Brown, Black and Silver

120V - 277V AC

3000/4000K

15W

80+

60

No

120°

LUMILED 3030

>50,000 Hours

8 x 4 3/8 x 2 1/8"

203 x 111 x 54mm

Aluminum

Outdoor

Wall

-20 to +40°C

Powder coated finish

1300LM

- Three interchangeable covers: Wave,
- Wing and Scoop

SPECIFICATIONS

• cULus listed for wet locations

TLWMV15XWMZZ

5 years

cULus listed for wet locations

120V 00 c (UL) us


APPLICATIONS


- Exterior residential & commercial
- Entrance ways
- Hallway lighting
- Patio & deck Lights
- Hotel hallways & restaurants
- Stairways & lobbies



PRODUCT CODES

LED	COLOUR	FINISH
Outdoor	OF LED	BR - Brown
Sconce	3 - 3000K	BK - Black
	4 - 4000K	SV - Silver








111 [4 3/8"] 66 [2 5/8"] Wave



3 COVER OPTIONS (Sold seperately)



DIAGRAM



203 114 [4 1/2"] 73 [2 7/8"] 64 [2 1/2"] Scoop

Wing