

# Surface Mount Down Lights (ROUND)

The LED Surface Mount Down Light offers a streamlined solution for efficient lighting. Built-in Driver on Board (DOB) technology allows for easy ceiling installation without an external driver. Perfect for enhancing any residential or commercial space.



## FEATURES

- DOB technology provides a 120V alternating current source and eliminates the need for traditional LED driver
- Quick & easy to install on standard junction box, ceiling mount with mounting plate
- Temperature rating: -20° to 40°C
- Die-cast aluminum housing
- Smooth and continuous dimming with most ELV dimmers
- Rated for 50,000 hours
- No light bulbs to replace or dispose
- Instant full brightness (including in sub-zero temperatures)
- 80+ CRI
- cETLus listed for wet locations
- 5 years limited warranty

## APPLICATIONS

- |   |  |
|---|--|
| <b>RESIDENTIAL</b>  | <b>COMMERCIAL</b>  |
| <ul style="list-style-type: none"> <li>• Kitchens</li> <li>• Pantries</li> <li>• Laundry rooms</li> <li>• Under cabinet</li> <li>• In cabinet</li> <li>• Under soffits (Outdoor)</li> </ul> | <ul style="list-style-type: none"> <li>• Lobbies &amp; hallways</li> <li>• Banquet halls</li> <li>• Elevators &amp; stairways</li> <li>• Retail &amp; restaurants</li> <li>• Under cabinet</li> <li>• In cabinet</li> <li>• Wall mount for regress lighting</li> </ul> |

## SPECIFICATIONS

Size	6 Inches	8 Inches	10 Inches	12 Inches
<b>Product Code</b>	LVLDL-SR-06-XX-WH-L	LVLDL-SR-08-XX-WH-L	LVLDL-SR-10-XX-WH-L	LVLDL-SR-12-XX-WH-L
<b>Electrical</b>	120V AC			
<b>Input Voltage</b>	120V AC			
<b>Power Consumption</b>	11W	14W	17W	22W
<b>Specs</b>	3000/4000K			
<b>Color Temperature</b>	3000/4000K			
<b>Lumen Output</b>	880WW, 900NW	1000WW, 1050NW	1200WW, 1250NW	1800WW, 1850NW
<b>Efficacy</b>	80WW, 82NW	71WW, 75NW	70WW, 73NW	82WW, 84NW
<b>CRI</b>	80+			
<b>Dimmable</b>	Yes (with most ELV dimmers)			
<b>Beam Angle</b>	N/A			
<b>LED</b>	Epistar			
<b>Type</b>	Epistar			
<b>Life Span</b>	50,000 Hours			
<b>Design</b>	Die-cast aluminum housing			
<b>Dimensions (Inches)</b>	6" D x 1" H	8" D x 1" H	10" D x 1" H	12" D x 1" H
<b>Dimensions (Millimeters)</b>	152mm D x 25mm H	203mm D x 25mm H	254mm D x 25mm H	305mm D x 25mm H
<b>Product Material</b>	Die-cast aluminum housing			
<b>Trim Finish</b>	BK: Black, BZ: Bronze, BN: Brushed Nickel			
<b>Operating Temperature</b>	-20°C to 40°C			
<b>Approved Location</b>	Kitchens, pantries, laundry rooms, under soffits (outdoors)			
<b>Mounting</b>	Surface			
<b>Warranty</b>	5 years			
<b>Approvals</b>	cETLus listed for wet locations and Energy Star			

## PRODUCT CODES

LVLDL - SR - YY - XX - WH - L

Round LED Surface Mount Down Light	SIZE 06 - 6" 08 - 8" 10 - 10" 12 - 12"	LED Colour WW: 3000K NW: 4000K
------------------------------------	--	--------------------------------------

**ROUND TRIM RINGS (Sold Separately)**  
 LVLDL - SR - 06 - TR - XX - L  
 LVLDL - SR - 08 - TR - XX - L  
 LVLDL - SR - 10 - TR - XX - L  
 LVLDL - SR - 12 - TR - XX - L

**TRIM RING FINISH**  
 BK: Black, BZ: Bronze, SN: Satin Nickel

## DIAGRAM

