# **LED Hard Strip RGB**

Designed for simplicity and efficiency, this LED strip provides a wide beam of light in a durable aluminum casing, with sizes to fit various spaces.

#### FEATURES

- High-brightness LEDs: 0.5W SMD PLCC-2 for powerful lighting.
- Wide spread: 120° angle for even light distribution.
- 24V DC: Low voltage operation.

• Versatile sizes: 11.8", 19.7", 39.4" for multiple applications.

- Easy connect: Connector for linking two strips
  - Cabinet interiors

the state of the law with the with the with the fully have

• Work stations

APPLICATIONS

• Under counter


• Display cases


Linear interior decorative lighting

Intertek

		SPECIFICATIONS			
		300mm	500mm	1000mm	
Product code	LV-HS-RGB-24T2-X	LV-HS-RGB-24T2-1	LV-HS-RGB-24T2-2	LV-HS-RGB-24T2-3	
Electrical	Input Voltage	24V DC			
	Power Consumption	3.6W	6W	12W	
Specs	Colour Temperature	RGB			
	Viewing Angle	120°			
LED	Туре	SMD PLCC-2			
	Life Span	N/A			
	Qty. per strip	18	30	60	
Design	Size (Inches)	11.81 x 0.63 x 0.83"	19.69 x 0.63 x 0.83"	39.37 x 0.63 x 0.83"	
	Size (Millimeters)	300 x 16 x 21mm	500 x 16 x 21mm	1000 x 16 x 21mm	
	Product Material		N/A		
	Operating Temperature		N/A		
	Mounting		N/A		
Warranty	N/A				
Approvals	cETLus for indoor use				

#### MOUNTING OPTIONS





PRODUCT CODES

- - 3= 1000mm



#### 

#### DIMMABLE DRIVERS

MLDRE-40-24-DM Max recommended load 36W, min. 8W LED Hard Strip 6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

#### MLDRE-96-24-DM

Max recommended load 90W, min. 8W LED Hard Strip 6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

### NON DIMMABLE DRIVERS

MLDR-120-24 Indoor/Outdoor driver combined two secondary taps. 120W hardwire Input: 100 - 240V AC Output: 24V DC

## ACCESSORIES



Hard Strip RGB, Bar - Hard

wire power supply





LV-HS-PF2-HW 39" Power Feed for LED

LV-HS-PC2-3 3" Power Connector for LED Hard Strip RGB, Bar - Bar

Ś

LV-HS-PC2-12 Bar - Bar



LV-HS-MC0 Mounting clip (2pk) LV-HS-MC30 Mounting clip 30° (2pk)

MIBOXER<sup>®</sup> Michael Statements New Head 3 in 1 LED Controller (WFI+2-40 Weather Full Statements) Michael Statements

**LN-WIFI-CTRL** 3 in 1 LED Strip Controller (WIFI + 2G)



G\$



LT-WIFI-AMP WiFi Signal Amplifier for RGB. RGBW. CCT



Three lengths available 11.8" (300mm), 19.7" (500mm), 39.4" (1000mr



Max. recommended load 90W per single tap, 120W

10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)

MLDR-20-24JB

Indoor driver Max recommended load 18W 20W hardwire Input: 100 – 240V AC Output: 24V DC 4 1/8" x 4 1/8" x 1 1/2" (104.8 x 104.8 x 38.1mm)




12" Power Connector for LED Hard Strip RGB,

G

LV-HS-MC45 Mounting clip 45° (2pk)



LV-HS-PC2-39 39" Power Connector for LED Hard Strip RGB, Bar - Bar



LV-HS-MCRT Rotary Mounting clip (2pk)



LV-HS-EC End Cap for LED Hard Strip



LN-WIFI-RM 4-Zone RGB+CCT Remote