5CCT LED Task Bar

For those seeking high performance LED under cabinet lighting fixture, the 5CCT LED Task Bar offers customizable lighting, true color representation, energy efficiency, easy installation, versatility, and durability.







FEATURES

- · Available in white finish
- Life: 35,000 Hours
- 120V Plug and cord and hardwire power cord available (sold separately)
- Easy installation
- 5 position switch for colour temperature
- Slim profile
- Dimmable with TRIAC dimmers
- Linkable up to 200W using end to end connectors or jumper cords
- Jumper cords available (sold separately)

APPLICATIONS


- Under cabinet task light
- Over cabinet accent light
- Display cases and exhibits
- Merchandising
- Wall units and bars
- Office work stations


| | | | SPECIFICA | ATIONS | | | |
|--------------|---------------------------|---------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|
| | | Size 1 | Size 2 | Size 3 | Size 4 | Size 5 | Size 6 |
| Product code | LEDLB-5CCT-XX | 10 Inches | 12 Inches | 18 Inches | 24 Inches | 36 Inches | 48 Inches |
| Electrical | Input Voltage | 120V AC | | | | | |
| | Power Consumption | 3.5W | 5W | 8W | 12W | 16W | 20W |
| | Max Wattage per run | 200W | | | | | |
| Specs | Colour Temperature | 2700/3000/3500/4000/5000K | | | | | |
| | CRI | 90 | | | | | |
| | Lumen Output | 290 | 443-541 | 652-771 | 966-1134 | 1199-1393 | 1599-1892 |
| | Efficacy (Lm/W) | 82.8 | 98.4 | 88.75 | 82.5 | 81.25 | 87.5 |
| | Dimmable | Yes, with TRIAC dimmers | | | | | |
| | Beam Angle | 110° | | | | | |
| LED | Туре | SMD2835 | | | | | |
| | Life Span | 35,000 Hours | | | | | |
| | Spacing | N/A | | | | | |
| | # per foot / unit | N/A | | | | | |
| Design | Dimensions Inches (I;h;w) | 9 3/4; 1 5/16; 13/16" | 12 3/8; 1 5/16; 13/16" | 17 1/2; 1 5/16; 13/16" | 22 5/8; 1 5/16; 13/16" | 347/16; 1 5/16; 13/16" | 46 1/4; 1 5/16; 13/16" |
| | Dimensions mm (I/h/w) | 247 / 33 / 20mm | 315 / 33 / 20mm | 445 / 33 / 20mm | 575 / 33 / 20mm | 875 / 33 / 20mm | 1175 / 33 / 20mm |
| | Finish Colour / trims | White | | | | | |
| | Product Material | Aluminum and acrylic | | | | | |
| | Max Single Run Length | 40Ft | | | | | |
| | Custom Cuttable | N/A | | | | | |
| | Operating Temperature | -20°C to 40°C | | | | | |
| | Approved Location | Damp | | | | | |
| | Mounting | Via included brackets | | | | | |
| Warranty | 5 years | | | | | | |
| Approvals | cETLus for indoor use | | | | | | |

NOTE: Only LEDLB-5CCT-18, LEDLB-5CCT-24, LEDLB-5CCT-36, and LEDLB-5CCT-48 have on/off switch.



DIAGRAM





20mm (13/16")

PRODUCT CODES

LEDLB - 5CCT - XX

SIZE

10, 12, 18, 24, 36, 48

ACCESSORIES

LEDLB-J-12 12" Jumper Cable

LEDLB-J-18 18" Jumper Cable

LEDLB-J-24 24" Jumper Cable

LEDLB-J-32 32" Jumper Cable



LTSPRO-PC-72 72" power cord and plug

LTSPRO-HW-72 72" power cord for hardwire



LTSPRO-JB Hardwire junction box With ON/OFF switch