

5CCT Fire Rated Regressed Downlight



This robust LED fire rated regressed downlight (with baffle) offers fire protection, adjustable colour temperature, dimming, and high colour accuracy. It's suitable for wet areas, operates in various temperatures, and ensures even lighting. The downlight includes a junction box with a commercial-grade driver for easy installation.

FEATURES

- 2-hour fire rating providing a reinforced and heat resistant steel casing.
- Tested to comply with UL 263, ASTM E119 & CAN/ULC S101-14.
- Two spring loaded clips to attach to any ceiling material.
- Selectable colour temperature: 2700K to 5000K.
- Wet locations listed.
- Triac dimmable.
- 5-year limited warranty.
- Airtight.
- cETLus and Energy Star listed.
- Junction box with commercial grade driver included.

APPLICATIONS

- Kitchens & pantries
- Laundry rooms
- Bathrooms
- Lobbies & hallways
- Banquet halls
- Elevators
- Retail lighting
- Offices & restaurants



SPECIFICATIONS		
Product Codes	RGL-FR-5CCT-4-WH	RGL-FR-5CCT-6-WH
Electrical	Input Voltage	120V AC
	Output Power (W)	12W / 15W
Specs	Colour Temperature	5-colour field selectable CCT: 2700K, 3000K, 3500K, 4000K, 5000K
	CRI	90+
	Lumens	1075Lm / 1418Lm
	Power Factor	>0.9
	Dimmable	Yes, with TRIAC dimmers
	Beam Angle	120°
LED	Type	Epistar
	Life Span	50,000 Hours
Design	Dimensions (Inches)	D1=3", D2=5", H=1/2" / D1=5", D2=7", H=1/2"
	Dimensions (Millimeters)	D1=81mm, D2=127mm, H=11.5mm / D1=126mm, D2=175mm, H=11.5mm
	Finish	White finish
	Trim Ring (Finish)	Brushed nickel and black trim rings - Sold separately
	Operating Temperature	-20° to 40°C (-4°F to 104°F)
	Approved Location	Wet
	Mounting	Ceiling
Warranty	5 Years	
Approvals	cETLus and Energy Star	



DIAGRAM

