

# Low Power Indoor (3000K)

This 3000K low-power indoor tape light is designed for high-efficiency lighting with a smooth, pixel-free and uniform output, making it ideal for refined indoor environments. Featuring dense 2219 LED chips on an 8mm wide PCB, it ensures consistent brightness and precise colour accuracy.




## FEATURES

- Delivers a soft, pixel-free 3000K light with more uniform output than standard tapes.
- Consumes 4.8W per meter.
- Slim 8mm wide, and 3mm high PCB.
- Maintains colour consistency with an SDCM<3.
- IP40 rating ensures protection against dust in indoor environments.
- Backed by a 5-year warranty.

## APPLICATIONS

- Under Cabinet
- Displays
- Cove (Low to Mild Ambient Light)
- Wall Grazing

SPECIFICATIONS		
<b>Product Code</b>		<ul style="list-style-type: none"> <li>• SL-ID-30K-LP-XX-A8 [XX: Length in feet; A: 2219 LED; 8: 8mm PCB]</li> <li>• Available in 20 or 100 feet; For 20 feet: SL-ID-30K-LP-20-A8; For 100 feet: SL-ID-30K-LP-100-A8</li> </ul>
<b>Electrical</b>	Input Voltage	24V DC
	Power Consumption	1.46W/ft (4.8 W/m)
	Efficacy	110Lm/w
<b>Specs</b>	Colour Temperature	3000K
	Lumen Output	160Lm/ft (528Lm/m)
	Beam Angle	140°
	Dimmable	Yes (PWM / 0-10V / 1-10V)
<b>LED</b>	Chip Type	2219
	CRI	90
	# per metre	288
	Binning	1BIN
	SDCM	<3
	Lifespan	50,000 Hours
<b>Design</b>	Dimensions (Inches)	.31" W
	Dimensions (Millimetres)	8mm W
	Max Length	40Ft (12M)
	Custom Cuttable	2.19" (55.5mm)
	IP Rating	IP40
	Approved Location	Indoor
<b>Warranty</b>		5 Years
<b>Approvals</b>		cULus



## ACCESSORIES



**SL-ID-W2BC-72**  
6' Powerfeed



**SL-ID-BWBC-6**  
6' Jumper



**SL-ID-B2BC**  
Splice



**SL-ID-LC**  
L-shaped Connector



**SL-ID-TC**  
T-shaped Connector

## DRIVERS

### Dimmable



**MLDRE-40-24-DM**  
Max. recommended load: 36W; Min. recommended load: 8W; 6.77" x 2.67" x 1.26" (171 x 68 x 32mm)



**MLDRE-96-24-DM**  
Max. recommended load: 90W; Min. recommended load: 8W; 6.77" x 2.67" x 1.26" (171 x 68 x 32mm)



**SX-24V-DD-100W**  
Switchex

### Non-Dimmable



**MLDR-120-24**  
Indoor/Outdoor driver  
Max. recommended load: 90W; 10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)



**MLDR-20-24JB**  
Indoor driver  
Max recommended load: 18W; 4 1/8" x 4 1/8" x 1 1/2" (104.8 x 104.8 x 38.1mm)



**PGID2448/PGID2496**  
Plug-in Driver

## CONTROLLERS



**CNTRL-0-10V-DIM**  
0/1-10V Dimming Controller



**CNTRL-4Z-CCT-RM**  
4 Zone CCT Remote



**CNTRL-4Z-CCT-RWP-WH OR CNTRL-4Z-CCT-RWP-BK**  
Rotating CCT Scene Remote (White or Black)