


CONTROLLERS

| | | | |
|------------------------------------|---------------------------------------------|------------------------------|-----------------------------------------|
| 3 in 1 LED Strip Controller | 5-Channel High Performance Amplifier | 4-Zone RGB+CCT Remote | 8 Zone RGB+CCT Wall Panel Remote |
| CNTRL-RGBCCT | CNTRL-AMP | CNTRL-4Z-RGBCCT-RM | CNTRL-8Z-RGBCCT-WP |

ACCESSORIES

| | | |
|-----------------------|----------------------|-----------------------------------|
| Mounting Clips | Silicone Glue | 1M SolidMounting Extrusion |
| SL-RGBW-MC | NFLX-GLUE | SL-RGBW-EX-39 |

DRIVERS
Non-Dimmable
**Plug-in Driver
 48W/96W:**

- PGID2448
- PGID2496

Indoor/Outdoor driver:

LEDDR-24-120W

Specifications

| | | | |
|-------------------|----------------------------------------------------------------------------------------------------------------------|--------------------------|-----------------|
| Input Voltage | 24V DC | SDCM | <3 |
| Power Consumption | <ul style="list-style-type: none"> • 2.19W/ft (7.2W/m) for RGB • 2.19W/ft (7.2W/m) for 3000K | Lifespan | 50,000 Hours |
| Efficacy | 70Lm/w | Dimensions (Inches) | .37" W |
| Color Temperature | RGB + 3000K | Dimensions (Millimeters) | 9.5mm W |
| Lumen Output | 153Lm/ft (504Lm/m) | Max Length | 40Ft (12M) |
| Beam Angle | 160° | Custom Cuttable | 2.19" (55.56mm) |
| Chip Type | 2835RGB + 2219WW | IP Rating | IP67 |
| CRI | 90 | Approved Location | Outdoor/Indoor |
| # per meter | 252 | Warranty | 5 Years |
| Binning | 1BIN | Approvals | cULus |

Ordering Code(s)

- SL-OD-RGB30K-XX-BA8 [XX: Length in feet; BA: 2835+2219 LED; 8: 8mm PCB]
 Available in 20 feet: SL-OD-RGB30K-20-BA8

| | | | |
|---------|--|---------|--|
| Project | | Type | |
| Date | | Contact | |
| Notes | | | |