



CONTROLLERS

3 in 1 LED Strip Controller	5-Channel High Performance Amplifier	4-Zone RGB+CCT Remote	8 Zone RGB+CCT Wall Panel Remote
CNTRL-RGBCCT	CNTRL-AMP	CNTRL-4Z-RGBCCT-RM	CNTRL-8Z-RGBCCT-WP

ACCESSORIES

ST-ID-RGB-BWBC-6	Splice	6' power feed
ST-ID-RGB-BWBC-6	ST-ID-RGB-B2BC	ST-ID-RGB-W2BC-72

DRIVERS Non-Dimmable

**Plug-in Driver
48W/96W:**

- PGID2448
- PGID2496

Indoor/Outdoor driver:

LEDDR-24-120W

Specifications

Input Voltage	24V DC	Dimensions (Inches)	.31" W
Power Consumption	4.39W/ft (14.4W/m)	Dimensions (Millimeters)	8mm W
Efficacy	36Lm/w	Max Length	20Ft (6M)
Color Temperature	RGB	Custom Cuttable	1.97" (50mm)
Lumen Output	158Lm/ft (518Lm/m)	Approved Location	Indoor
Beam Angle	120°	Warranty	5 Years
Chip Type	2835	# per meter	120
IP Rating	IP20	Approvals	cULus

Ordering Code(s)

- ST-ID-RGB-HP-XX-B8 [XX: Length in feet; B: 2835 LED; 0: 10mm PCB]
Available in 20 feet: ST-ID-RGB-HP-20-B8

Project		Type	
Date		Contact	
Notes			