

High Power and Low Power Indoor (3000K)

Available in High Power and Low Power models, these indoor LED tape lights deliver smooth, pixel-free illumination and are ideal for a wide range of lighting fixtures. Built with dense 2219 LED chips and engineered for consistent colour output, both options offer reliable, long-lasting performance.



FEATURES


- Dense 2219 LEDs per meter for seamless, uniform lighting.
- 3000K warm white with CRI 90+.
- SDCM <3, 1 BIN selection for uniformity.
- Slim 8mm wide PCB for tight spaces.

- IP40 rated for protected indoor environments.
- cULus listed for safety and quality assurance.
- 5-year product warranty.

APPLICATIONS

- Under Cabinet
- Displays
- Coves
- Wall Grazing
- Architectural Features

SPECIFICATIONS			
Product Code		SL-ID-30K-LP-XX-A8 [XX: Length in feet; A: 2219 LED; 8: 8mm PCB] Available in 20 or 100 feet; For 20 feet: SL-ID-30K-LP-20-A8; For 100 feet: SL-ID-30K-LP-100-A8	SL-ID-30K-HP-XX-A8 [XX: Length in feet; A: 2219 LED; 8: 8mm PCB] Available in 20 or 100 feet; For 20 feet: SL-ID-30K-HP-20-A8; For 100 feet: SL-ID-30K-HP-100-A8
Electrical	Input Voltage	24V DC	
	Power Consumption	2.93W/ft (9.6W/m)	1.46W/ft (4.8 W/m)
	Efficacy	102Lm/w	110Lm/w
Specs	Colour Temperature	3000K	
	Lumen Output	300Lm/ft (980Lm/m)	160Lm/ft (528Lm/m)
	Beam Angle	140°	
	Dimmable	Yes (PWM / 0-10V / 1-10V)	
LED	Chip Type	2219	
	CRI	90	
	# per metre	288	
	Binning	1BIN	
	SDCM	<3	
	Lifespan	50,000 Hours	
Design	Dimensions (Inches)	.31" W	
	Dimensions (Millimeters)	8mm W	
	Max Length	20Ft (6M)	
	Custom Cuttable	2.19" (55.5mm)	
	IP Rating	IP40	
	Approved Location	Indoor	
Warranty		5 Years	
Approvals		cULus	



ACCESSORIES



SL-ID-W2BC-72
6' Powerfeed



SL-ID-BWBC-6
6" Jumper



SL-ID-B2BC
Splice



SL-ID-LC
L-shaped Connector



SL-ID-TC
T-shaped Connector

DRIVERS

Dimmable



MLDRE-40-24-DM
Max. recommended load: 36W; Min. recommended load: 8W;
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)



MLDRE-96-24-DM
Max. recommended load: 90W; Min. recommended load: 8W;
6.77" x 2.67" x 1.26" (171 x 68 x 32mm)



SX-24V-DD-100W
Switchex

Non-Dimmable



MLDR-120-24
Indoor/Outdoor driver
Max. recommended load: 90W;
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)



MLDR-20-24JB
Indoor driver
Max recommended load: 18W;
4 1/8" x 4 1/8" x 1 1/2" (104.8 x 104.8 x 38.1mm)



**PGID2448/
PGID2496**
Plug-in Driver

CONTROLLERS



CNTRL-0-10V-DIM
0/1~10V Dimming Controller



CNTRL-4Z-CCT-RM
4 Zone CCT Remote



**CNTRL-4Z-CCT-RWP-WH
OR
CNTRL-4Z-CCT-RWP-BK**
Rotating CCT Scene Remote
(White or Black)