



ACCESSORIES	
6" Jumper	ST-10MM-BWBC-6
Splice	ST-10MM-B2BC
6' power feed	ST-10MM-W2BC-72

DRIVERS	
Dimmable	
Dimmable Electronic LED Driver:	<ul style="list-style-type: none"> TRE24L40D TRE24L96DC
Switchex	SX-24V-DD-100W
Non-Dimmable	
Plug-in Driver	<ul style="list-style-type: none"> PGID2448 PGID2496
Indoor/Outdoor driver	LEDDR-24-120W

ACCESSORIES	
0/1 ~ 10V Dimming Controller	ST-10MM-BWBC-6

Specifications			
Input Voltage	24V DC	Binning	1BIN
Power Consumption	2.19W/ft (7.2W/m)	SDCM	<2
Efficacy	120Lm/w	Lifespan	50,000 Hours
Color Temperature	2700K and 3000K	Dimensions (Inches)	.39" W
Lumen Output	263Lm/ft (864Lm/m)	Dimensions (Millimeters)	10mm W
Beam Angle	120°	Max Length	40Ft (12M)
Dimmable	Yes, via controllers	Custom Cuttable	3.94" (100mm)
Chip Type	2835	IP Rating	IP20
CRI	90	Approved Location	Indoor
# per meter	80	Warranty	5 Years

Ordering Code(s)

- ST-ID-27K-LP-XX-B0 [XX: Length in feet; B: 2835 LED; 0: 10mm PCB] / Available in 20 feet: ST-ID-27K-LP-20-B0
- ST-ID-30K-LP-XX-B0 [XX: Length in feet; B: 2835 LED; 0: 10mm PCB] / Available in 20 feet: ST-ID-30K-LP-20-B0

Project		Type	
Date		Contact	
Notes			